

solareye post

thesolarrange

INTELLIGENT SOLAR LIGHTING

Eco-friendly post mounted delineator.

solar powered lighting that gently illuminates and outlines cycle paths, footpaths and driveways

FEATURES

Aluminium post 700 x 150 x 50mm
3mm wall thickness
Aluminium base plate including fixings
Powder coated RAL 7016 anthracite grey

Solareye 2 off solareyes flush fitted single sided steady
white LED 100,000 hours
8 year battery life
Dusk to dawn illumination
Working temperature -20c to 70c
100mm diameter
IP68

SPECIFICATIONS

Pole distance	12.000 m
(1) Light spot height	0.375 m
(2) Light point overhang	0.000 m
(3) Boom inclination	0.0°
(4) Boom length	0.080 m
Annual operating hours	1825 h: 100.0 %, 0.0 W
Consumption	0.0 W/km
ULR / ULOR	0.04 / 0.04
Max. luminous intensities	≥ 70°: 146 cd/klm
	≥ 80°: 130 cd/klm
	≥ 90°: 68.5 cd/klm

Any direction forming the specified angle from the downward vertical, with the luminaire installed for use.

Luminous intensity class

-
The luminous intensity values in [cd/klm] for calculation of the luminous intensity class refer to the luminaire luminous flux according to EN 13201:2015.

Glare index class

D.6

